

PRODUCT INFORMATION PACKET



Model No: 6503V

Catalog No: 6503V

EVERGREEN® VS Fan and Blower Motor, 1/3 HP, 1 Ph, 60/50 Hz, 120/240 V, 1050 RPM, 5 Speed, 48 Frame, OPAO



Regal and Genteq are trademarks of Regal Rexnord Corporation or one of its affiliated companies.
©2026 Regal Rexnord Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Phase	1	Output HP	1/3 Hp
Output KW	0.25 kW	Voltage	120/240 V
Speed	1050 rpm	Service Factor	1
Frame	48	Enclosure	Open Air Over
Thermal Protection	Automatic	Ambient Temperature	40 °C
Frequency	60/50 Hz	Current	5.0/2.8 A
Duty	Continuous Air Over	Insulation Class	B
UL	No	CSA	N
CE	Y	A2L Status	A2L Certified
Number of Speeds	5		

Technical Specifications

Electrical Type	Electronically Commutated Motor	Poles	12
Rotation	Counterclockwise/Clockwise	Mounting	Round
Motor Orientation	Vsd	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	Flat	Overall Length	10.71 in
Frame Length	3.57 in	Shaft Diameter	0.500 in
Shaft Extension	5.00 in		
Outline Drawing	5SME39DXL3226	Connection Drawing	N/R

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:09/02/2026

CONNECTOR ID

DESCRIPTION

+V

12V INPUT

Tx

SERIAL DATA OUTPUT

Rx

SERIAL DATA INPUT

C

COMMON

JMP

JUMPER APPLICATION FOR 120VAC LINE INPUT ONLY
SEE NOTE 4

GROUND

N

AC LINE

L1

AC LINE

SEE NOTE 2

SEE TABLE FOR CONNECTION DEFINITIONS

VIEW A-A

NOTE - 1

- FOR VUI MOTOR (5SME39DXL3226A), USE #CPN 6503VUI
- FOR VS MOTOR (5SME39DXL3226), USE #CPN 6503V

NAMEPLATE DATA

MODEL	SEE NOTE-1
STOCK NO	SEE NOTE-1
HP	1/3
RPM	1050
VOLTS	120/240
HZ	60/50
AMPS	5.0/2.8
ROTATION	CCW/CW
MTG. POSITION	VSD

NOTES:

- BELLY BAND MUST BE PLACED WITHIN AREA "A" ONLY
- OPTIONAL EXTERNAL #8 SELF TAPPING GROUND SCREW AND TERMINAL MAY BE PROVIDED BY CUSTOMER AT LOCATION SHOWN.
- SUGGESTED MATING CONNECTORS:
5 PIN CONNECTOR - TYCO 350809-1
4 PIN CONNECTOR - TYCO 350779-1
SOCKET (TIN) - FOR .060-.130 WIRE INS. DIA RANGE - TYCO 350536-1
FOR .130-.200 WIRE INS. DIA RANGE - TYCO 350537-1
- WARNING: APPLYING 240VAC LINE INPUT WITH JUMPER APPLIED WILL PERMANENTLY DAMAGE UNIT.

DRAWING REVISION
F

REVISION BY
SAI KIRAN.R

REV DATE/© DATE
8/7/2023

REQUEST NUMBER
ECR-0227061

APPROVED BY
DON.S

DATE
8/7/2023

REQUEST NUMBER DESCRIPTION
UPDATED AS PER ECR-0227061

COPYRIGHT (PER REVISION DATE) REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

PRIMARY DIMENSIONS ARE INCH
mm DIMENSIONS IN [BRACKETS]
ARE FOR REFERENCE ONLY

DRAWN BY
KEP

DATE
11/22/2017

APPROVED BY
ANDREA

DATE
11/22/2017

REFERENCE
-

THIRD ANGLE PROJECTION

Regal Rexnord

Regal Beloit America, Inc.

DESCRIPTION
OUTLINE
ECM EVERGREEN VUI

MATERIAL
-

PROCESS/FINISH
-

SIZE
B

DRAWING NUMBER
5SME39DXL3226

SHEET
1 OF 1

10.71

5.00

4.50

3.57

5.71

"C"

"N"

"K"

"XA"

"AG"

4

3

2

1

3 of 3